

## Certificate of Registration

**Certificate Number 472**

Placed on the Market under the Name of

**Youngs Doors Ltd  
City Road Works  
City Road  
Norwich  
NR1 3AN  
UNITED KINGDOM**

and produced in the manufacturing plants

**Factory 1: Youngs Doors Ltd, City Road Works, Norwich. NR1 3AN United Kingdom**

**Factory 2: Youngs Doors Ltd, Bullen Joinery, Central Road, Cromer, Norfolk. NR27 9BW  
United Kingdom**

This certificate attests that all provisions have been met concerning the BM TRADA requirements of the scheme:

**Q-Mark Timber Fire Door Manufacture**

Date of Initial Certification: **27/08/2010**

Date of Last Issue: **16/06/2025**

Date of Expiry: **26/08/2028**



**Jon Lessimore (Divisional Director)**  
For and on behalf of Element

## Scope of Certification

### Primary Field of Application (FoA) Reports (owned by this certified company)

Either used in isolation, or can be used in conjunction with an appropriate associated document for this company, providing that the FoA report allows it and that both documents are compatible with each other. Where more than one primary FoA is listed for the same doorset type, they cannot be mix and matched, only one FoA is to be chosen and followed precisely

Type	FoA Report	Rev	Owned by Certified Company named on this scope	Doorset Description	Integrity Period	FoA Standard
Fire	N/A	-	-	-	-	-
Smoke	N/A	-	-	-	-	-

### Primary Field of Application (FoA) Reports (owned by and cascaded by a System Supplier)

The revision status of each FoA can be verified on the BM TRADA website under each System Supplier's certification entry. They are either used in isolation, or can be used in conjunction with an appropriate associated document for this company, providing that the FoA report allows it and that both documents are compatible with each other. Where more than one primary FoA is listed for the same doorset type, they cannot be mix and matched, only one FoA is to be chosen and followed precisely.

Type	FoA Report	System Supplier owner of Assessment Report	Doorset Description	Integrity Period	FoA Standard
Fire	Chilt/A02066	Falcon Timber Limited	STREbord® 44 door assemblies for 30 Minutes Fire Resistance (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A02066	Falcon Timber Limited	STREbord® 54 door assemblies for 30 Minutes Fire Resistance (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A02067	Falcon Timber Limited	STREbord® 54 doorsets for 60 Minutes Fire Resistance (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A10152	Falcon Timber Limited	STREbord® 54 Panelled Range of Doorsets using STREbord® 54 Panelled Door Blanks in Timber Based Door Frames 60 Minutes Fire Resistance (Unglazed only)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	BMT/CNA/F15159	Falcon Timber Limited	STREdor® 44 doorsets for 30 Minutes Fire Resistance (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	WF377027	Falcon Timber Limited	STREdor® 54 Doorsets for 30 Minutes Fire Resistance (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	WF377027	Falcon Timber Limited	STREdor® 54 Doorsets for 60 Minutes Fire Resistance (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	WF380559	Falcon Timber Limited	STREbord® 35+ doorsets for 30 Minutes Fire Resistance (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A01204	Halspan Limited	Optima 30 Part 1 Timber (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A01205	Halspan Limited	Optima 60 (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	FEA/F97174	Halspan Limited	Prima 30 Part 1 Timber (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	FEA/F96103	Halspan Limited	Prima 60 Part 1 Timber (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	BMT/CNA/F15082	Halspan Limited	Halspan 120 (Glazed or Unglazed)	120min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A13242	Halspan Limited	Halspan XT30 and IT30 30 minute fire resisting doorsets (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	Chilt/A13227	Halspan Limited	Halspan XT60, IT60, XT60 Head Rail and XT60R 60 minute fire resisting doorsets (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	FEA98164	Pacific Rim Wood Ltd	The Flamebreak Range of Doorsets Using Timber Based Door Blanks in Timber Based Door Frames for 30 minutes Fire Resistance (Glazed or unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	FEA/F02141	Pacific Rim Wood Ltd	Flamebreak 660 Ply Faced and FF660 MDF Faced Doorset Ranges in Timber Based Door Frames for 60 minutes Fire Resistance (Glazed or unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	BMT/CNA/F14274	Moralt AG	LAMINESSE FireSound 44mm (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	WF409922	Moralt AG	LAMINESSE FireSound 54mm (Glazed or Unglazed)	30min	BS 476 Pt22
Smoke	N/A	-			N/A
Fire	WF409922	Moralt AG	LAMINESSE FireSound 54mm (Glazed or Unglazed)	60min	BS 476 Pt22
Smoke	N/A	-			N/A

Fire	WF409922	Moralt AG	LAMINESSE FireSound 59mm (Glazed or Unglazed)	30min	BS 476 Pt22 N/A
Smoke	N/A	-			
Fire	WF409922	Moralt AG	LAMINESSE FireSound 59mm (Glazed or Unglazed)	60min	BS 476 Pt22 N/A
Smoke	N/A	-			
Fire	WF409922	Moralt AG	LAMINESSE FireSoundPlus 54 (Glazed or Unglazed)	30min	BS 476 Pt22 N/A
Smoke	N/A	-			
Fire	WF409922	Moralt AG	LAMINESSE FireSoundPlus 54 (Glazed or Unglazed)	60min	BS476 Pt22 N/A
Smoke	N/A	-			
Fire	FEA/F99112	Vicaima Ltd	Vicaima 30-minute Timber Based Doorsets (Glazed or Unglazed)	30min	BS 476 Pt22 N/A
Smoke	N/A	-			
Fire	WF509173	Starbank Panel Products Ltd	The Shield® Encapsulated Range of Doorsets Using Timber Based Door Blanks in Timber Based Door Frames (Glazed or unglazed)	30min	BS 476 Pt22 N/A
Smoke	-	-			
Fire	WF509174	Starbank Panel Products Ltd	The Shield® Encapsulated Range of Doorsets Using Timber Based Door Blanks in Timber Based Door Frames (Glazed or unglazed)	60min	BS 476 Pt22 N/A
Smoke	-	-			
Fire	BMT/CNA/F15084	Winkhaus UK Ltd	Winkhaus Timber Frame with Halspan Blank (Glazed or unglazed)	30min	BS 476 Pt22 -
Smoke	N/A	-			
Fire	BMT/CNA/F15084	Winkhaus UK Ltd	Winkhaus Timber Frame with Halspan Blank (Unglazed Only)	60min	BS 476 Pt22 -
Smoke	N/A	-			
Fire	Chilt/A12005	Safehinge Primera	Safehinge™ Alumax combined with Timber Frames (Glazed or Unglazed)	30min	BS 476 Pt22 N/A
Smoke	N/A	-			
Fire	Chilt/A12005	Safehinge Primera	Safehinge™ Alumax combined with Timber Frames (Glazed or Unglazed)	60min	BS 476 Pt22 N/A
Smoke	N/A	-			

**Test Reports**

Test reports cannot be used in conjunction with any primary FoA reports, other test reports or associated documents. They must be followed precisely without any deviation whatsoever.

**No specification or parameter changes are allowed at all from that stated within the test report such as size, shape, design, glazing, leaf/frame specification, hardware etc.**

Type	Test Report	Owner of Test Report	Doorset Description	Integrity Period	Test Standard
Fire only	N/A	-	-	-	-